



# DECLARATION OF PERFORMANCE

No OC

Unique identification code of the product-type:

CEKOL OC-01 GP CSIV W1

Intendent use or uses:

Render based on in-organic binders (cement, lime). For internal and external use. For manual and mechanical application

Manufacturer:

CEDAT Spółka z o.o., 80-298 Gdańsk, ul. Budowlanych 19, tel. +48 58 768 21 01, e-mail: [technologia@cekol.pl](mailto:technologia@cekol.pl)

Authorised representative: not applicable

System/s of AVCP:

System 4

Harmonised standard:

EN 998-1:2016 Specification for mortar for masonry – Part 1: Rendering and plastering mortar

Notified body or bodies: not applicable

Declared performance/s:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 998-1:2016
Thermal conductivity, $\lambda_{10, \text{dry mat}}$	1,11 W/m-K for P=50% (average tabulated value: EN1745:2012, Table A.12)	
Density, kg/m <sup>3</sup>	1970	
Water absorption	W <sub>c</sub> 1	
Water vapour permeability, $\mu$	15/35 (average tabulated value: EN1745:2012, Table A.12)	
Adhesion	0,5 N/mm <sup>2</sup> FP-B	
Durability, decrease of mass after freeze/thaw cycles	≤ 2%	
Dangerous substances	Contains cement	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Anna Gutek, Director of Quality Control

Gdańsk, 20.12.2019

(Place and date of issue)

DYREKTOR  
KONTROLI JAKOŚCI

*A. Gutek*  
mgr inż. Anna Gutek  
(Signature)