



DECLARATION OF PERFORMANCE

No ZK-1

Unique identification code of the product-type:

CEKOL ZK-1 G M15

Intendent use or uses:

General purpose prescribed masonry mortar (G)

Manufacturer:

CEDAT Spółka z o.o., 80-298 Gdańsk, ul. Budowlanych 19, tel. +48 58 768 21 01, e-mail: technologia@cekol.pl

Authorised representative: not applicable

System/s of AVCP:

System 4

Harmonised standard:

EN 998-2:2016 Specification for mortar for masonry – Part 2: Masonry mortar

Notified body or bodies: not applicable

Declared performance/s:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 998-2:2016
Water absorption	$\leq 0,15 \text{ kg/m}^2 \cdot \text{min}^{0,5}$	
Water vapour permeability, μ	15/35 (tabulated value: EN1745:2012, Table A.12)	
Thermal conductivity	1,11 W/m·K for P=50% (tabulated value: EN1745:2012, Table A.12)	
Density, kg/m^3	2060	
Durability – decrease of mass after freeze/thaw cycles	$\leq 3 \%$	
Proportion of constituents, cement/aggregate (by weight)	1:5	
Content of chloride	$< 0,1 \%$	
Dangerous substances	Contains cement	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Anna Gutek, Director of Quality Control

Gdańsk, 20.12.2019

(Place and date of issue)

DYREKTOR
KONTROLI JAKOŚCI

mgr inż. Anna Gutek
(Signature)