



DECLARATION OF PERFORMANCE

No ZS-06

Unique identification code of the product-type:

CEKOL ZS-06 GP CSIV W1

Intendent use or uses:

General purpose render (GP), mixed in factory. Use in masonry walls, columns and partitions, external and internal buildings

Manufacturer:

CEDAT Spółka z o.o., 80-298 Gdańsk, ul. Budowlanych 19, tel. +48 58 768 21 01, e-mail: technologia@cekol.pl

Authorised representative: not applicable

System/s of AVCP:

System 4

Harmonised standard:

EN 998-1:2016 Specification for mortar for masonry – Part 1 Rendering and plastering mortar

Notified body or bodies: not applicable

Declared performance/s:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 998-1:2016
Water absorption	W _c 1	
Adhesion	≥ 0,3 N/mm ² , FP-B	
Water vapour permeability	≤ 16,8	
Thermal conductivity, λ _{10,dry mat.}	0,45 W/m·K for P=50% (average tabulated value: EN1745:2012, Table A.12)	
Density, kg/m ³	1400	
Durability, decrease of mass after freeze/thaw cycles	≤ 2%	
Dangerous substances	Contains cement	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Anna Gutek, Director of Quality Control

Gdańsk, 23.12.2019.....

(Place and date of issue)

DYREKTOR
KONTROLI JAKOŚCI

A. Gutek
mgr inż. Anna Gutek

(Signature)