



# DECLARATION OF PERFORMANCE

No ZW-05

Unique identification code of the product-type:

CEKOL ZW-05 OC CSIV W1

Intendent use or uses:

One coat render for internal and external use, OC CSIV W1

Manufacturer:

CEDAT Spółka z o.o., 80-298 Gdańsk, ul. Budowlanych 19, tel. +48 58 768 21 01, e-mail: [technologia@cekol.pl](mailto:technologia@cekol.pl)

Authorised representative: not applicable

System/s of AVCP:

System 4

Harmonised standard:

EN 998-1:2016 Specification for mortar for masonry – Part 1 Rendering and plastering mortar

Notified body or bodies: not applicable

Declared performance/s:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1/A1 <sub>n</sub>	EN 998-1:2016
Water absorption coefficient due to capillary action	W <sub>c</sub> 2	
Adhesion after weathering cycles	≥ 0,7 N/mm <sup>2</sup> , FP-B	
Water vapour permeability	≤ 18,4	
Thermal conductivity	0,61 W/m·K for P=50% (average tabulated value: EN 1745:2012, Table A.12)	
Density, kg/m <sup>3</sup>	1590	
Durability, decrease of mass after freeze/thaw cycles	≤ 2%	
Water permeability after weathering cycles	≤ 1 ml/cm <sup>2</sup> after 48h	
Dangerous substances	Contains cement	

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Anna Gutek, Director of Quality Control

Gdańsk, 20.12.2019

(Place and date of issue)

DYREKTOR  
KONTROLI JAKOŚCI

mgr inż. Anna Gutek

(Signature)